

JC14 Rec'd PCT/PTO 07 JAN 2002

FORM PTO-1390 (REV 10-94)		U S DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE		DOCKET #: 4925-198PUS
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371				
				U.S. APPLICATION NO. (If known, see 37 CFR 1.5) 107030352
INTERNATIONAL APPLICATION NO PCT/IB00/01719 ✓		INTERNATIONAL FILING DATE 07 July 2000 ✓		PRIORITY DATE CLAIMED 09 July 1999 ✓
TITLE OF INVENTION Placement of Idle Periods				
APPLICANT(S) FOR DO/EO/US Kari KALLIOJARVI; Isabella MODONESI ✓				
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information: 1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. 2. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371 3. <input checked="" type="checkbox"/> This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1). 4. <input checked="" type="checkbox"/> A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date. 5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2)) a. <input checked="" type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau). b. <input type="checkbox"/> has been transmitted by the International Bureau. c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US) 6. <input type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)). 7. <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)) a. <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau). b. <input type="checkbox"/> have been transmitted by the International Bureau. c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. d. <input checked="" type="checkbox"/> have not been made and will not be made. 8. <input type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). 9. <input checked="" type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). Unexecuted 10. <input type="checkbox"/> A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)). Items 11. to 16. Below concern other document(s) or information included: 11. <input checked="" type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98. 12. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. 13. <input checked="" type="checkbox"/> A FIRST preliminary amendment. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment. 14. <input type="checkbox"/> A substitute specification. 15. <input type="checkbox"/> A change of power of attorney and/or address letter. 16. <input checked="" type="checkbox"/> Other items or information (<i>specify</i>): PCT Publication Sheet, Int'l Preliminary Examination Report, Int'l Search Report, PCT Request, and PCT Demand				

U.S. APPLICATION NO. (If known, see 37 CFR 1.5) <div style="font-size: 2em; font-weight: bold; margin-top: 10px;">10/030352</div>		INTERNATIONAL APPLICATION NO PCT/IB00/01719		ATTORNEY'S DOCKET NUMBER 4925-198PUS	
17.[x]The following fees are submitted:					
Basic National Fee (37 CFR 1.492(a)(1)-(5)): Search Report has been prepared by the EPO or JPO\$890.00 International preliminary examination fee paid to USPTO (37 CFR 1.482).....\$710.00 No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2)).....\$740.00 Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO\$1040.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4)\$100.00					
ENTER APPROPRIATE BASIC FEE AMOUNT =				\$	890
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).				\$	
Claims	Number Filed	Number Extra	Rate		
Total Claims	79 - 20 =	59	x \$18.00	\$	1062
Independent Claims	1 - 3 =	0	x \$84.00	\$	
Multiple dependent claim(s) (if applicable)			+ \$280.00	\$	
TOTAL OF ABOVE CALCULATIONS =				\$	1952
Reduction of 1/2 for filing by small entity, if applicable.				\$	
SUBTOTAL =				\$	1952
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$	
TOTAL NATIONAL FEE =				\$	1952
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by the appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property				\$	
TOTAL FEES ENCLOSED					\$1952
				Amount to be refunded:	\$
				charged:	\$
a. [x] One check in the amount of \$ <u>1952</u> to cover the above fee is enclosed. b. <input type="checkbox"/> Please charge my Deposit Account No. <u>03-2412</u> in the amount of \$ _____ to cover the above fees. A duplicate copy of this sheet is enclosed. c. [x] The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. <u>03-2412</u> . A duplicate copy of this sheet is enclosed.					
NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.					
SEND ALL CORRESPONDENCE TO: <u>Michael C. Stuart</u> Cohen, Pontani, Lieberman & Pavane 551 Fifth Avenue, Suite 1210 New York, New York 10176			<div style="text-align: center;"> </div> <u>Michael C. Stuart</u> <u>Registration Number: 35,698</u> <u>January 7, 2002</u> Tel: (212) 687-2770		

10/030352

JC10 Rec'd PCT/PTO 07 JAN 2002

By Express Mail # EV052763365US · January 7, 2002

Attorney Docket # 4925-198PUS

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re National Phase PCT Application of

Kari KALLIOJARVI et al.

International Appln. No.: PCT/IB00/01719

International Filing Date: 07 July 2000

For: Placement of Idle Periods

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231
BOX PCT

S I R:

Prior to examination of the above-identified application please amend the application as follows:

IN THE SPECIFICATION:

Page 1, line 2, Delete "Description" and insert the following heading:

--FIELD OF THE INVENTION--.

Page 1, before line 6, the paragraph beginning “It is known:”, insert the following heading:

--BACKGROUND OF THE INVENTION--.

Page 3, before line 6, the paragraph beginning “According to the present”, insert the following heading:

--SUMMARY OF THE INVENTION--.

Page 3, before line 15, the paragraph beginning “An embodiment”, insert the following paragraph and heading:

--Other objects and features of the present invention will become apparent from the following detailed description considered in conjunction with the accompanying drawings. It is to be understood, however, that the drawings are intended solely for purposes of illustration and not as a definition of the limits of the invention, for which reference should be made to the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS--.

Page 3, before line 20, the paragraph beginning “This embodiment relates”, insert the following heading:

--DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EMBODIMENT--.

Page 11, after line 20 (last line), insert the following paragraph:

-- Thus, while there have been shown and described and pointed out fundamental novel features of the present invention as applied to a preferred embodiment thereof, it will be understood that various omissions and substitutions and changes in the form and details of the devices described and illustrated, and in their operation, and of the methods described may be made by those skilled in the art without departing from the spirit of the present invention. For example, it is expressly intended that all combinations of those elements and/or method steps which perform substantially the same function in substantially the same way to achieve the same results are within the scope of the invention. Substitutions of elements from one described embodiment to another are also fully intended and contemplated. It is the intention, therefore, to be limited only as indicated by the scope of the claims appended hereto.--.

Page 12, line 1, delete "CLAIMS" and insert therefor "What is claimed is:--.

IN THE CLAIMS:

Cancel claim 14, without prejudice.

Amend claims 3 to 13 to read as follows:

3. A telecommunications system according to claim 1, wherein adjacent base stations within a group are assigned different frame numbers.

4. A telecommunications system according to claim 1, wherein adjacent base stations belonging to different groups are assigned different frame numbers.

5. A telecommunications system according to claim 1, wherein all the base stations within one group are assigned the same slot number or numbers.

6. A telecommunications system according to claim 1, wherein each frame comprises 15 slots and geographically adjacent groups are assigned slots which are spaced apart by at least one slot period.

7. A telecommunications system according to claim 1, each of the transmitters of each group being assigned more than one frame number.

8. A telecommunications system according to claim 1, in which each superframe comprises 72 frames.

9. A telecommunications system according to claim 1, wherein the transmitters operate asynchronously.

10. A telecommunications system according to claim 1, wherein in order to operate at reduced transmission power during the slot or slots assigned to its group in the frame assigned to it, each transmitter is arranged to undergo an idle period.

11. A telecommunications system according to claim 1, wherein each transmitter is arranged to operate at reduced transmission power for 0.667ms during the slot or slots assigned to its group in the frame assigned to it.

12. A telecommunications system according to claim 1, which is operable according to a W-CDMA system.

13. A telecommunications system according to claim 1, wherein the said period is longer than one slot.

Add the following new claims:

15. A telecommunications system according to claim 2, wherein adjacent base stations within a group are assigned different frame numbers.

16. A telecommunications system according to claim 2, wherein adjacent base stations belonging to different groups are assigned different frame numbers.

17. A telecommunications system according to claim 3, wherein adjacent base stations belonging to different groups are assigned different frame numbers.

18. A telecommunications system according to claim 2, wherein all the base stations within one group are assigned the same slot number or numbers.

19. A telecommunications system according to claim 3, wherein all the base stations within one group are assigned the same slot number or numbers.

20. A telecommunications system according to claim 4, wherein all the base stations within one group are assigned the same slot number or numbers.

21. A telecommunications system according to claim 2, wherein each frame comprises 15 slots and geographically adjacent groups are assigned slots which are spaced apart by at least one slot period.

22. A telecommunications system according to claim 3, wherein each frame comprises 15 slots and geographically adjacent groups are assigned slots which are spaced apart by at least one slot period.

23. A telecommunications system according to claim 4, wherein each frame comprises 15 slots and geographically adjacent groups are assigned slots which are spaced apart by at least one slot period.

24. A telecommunications system according to claim 5, wherein each frame comprises 15 slots and geographically adjacent groups are assigned slots which are spaced apart by at least one slot period.

25. A telecommunications system according to claim 2, each of the transmitters of each group being assigned more than one frame number.

26. A telecommunications system according to claim 3, each of the transmitters of each group being assigned more than one frame number.

27. A telecommunications system according to claim 4, each of the transmitters of each group being assigned more than one frame number.

28. A telecommunications system according to claim 5, each of the transmitters of each group being assigned more than one frame number.

29. A telecommunications system according to claim 6, each of the transmitters of each group being assigned more than one frame number.

30. A telecommunications system according to claim 2, in which each superframe comprises 72 frames.

31. A telecommunications system according to claim 3, in which each superframe comprises 72 frames.

32. A telecommunications system according to claim 4, in which each superframe comprises 72 frames.

33. A telecommunications system according to claim 5, in which each superframe comprises 72 frames.

34. A telecommunications system according to claim 6, in which each superframe comprises 72 frames.

35. A telecommunications system according to claim 7, in which each superframe comprises 72 frames.

36. A telecommunications system according to claim 2, wherein the transmitters operate asynchronously.

37. A telecommunications system according to claim 3, wherein the transmitters operate asynchronously.

38. A telecommunications system according to claim 4, wherein the transmitters operate asynchronously.

39. A telecommunications system according to claim 5, wherein the transmitters operate asynchronously.

40. A telecommunications system according to claim 6, wherein the transmitters operate asynchronously.

41. A telecommunications system according to claim 7, wherein the transmitters operate asynchronously.

42. A telecommunications system according to claim 8, wherein the transmitters operate asynchronously.

43. A telecommunications system according to claim 2, wherein in order to operate at reduced transmission power during the slot or slots assigned to its group in the frame assigned to it, each transmitter is arranged to undergo an idle period.

44. A telecommunications system according to claim 3, wherein in order to operate at reduced transmission power during the slot or slots assigned to its group in the frame assigned to it, each transmitter is arranged to undergo an idle period.

45. A telecommunications system according to claim 4, wherein in order to operate at reduced transmission power during the slot or slots assigned to its group in the frame assigned to it, each transmitter is arranged to undergo an idle period.

46. A telecommunications system according to claim 5, wherein in order to operate at reduced transmission power during the slot or slots assigned to its group in the frame assigned to it, each transmitter is arranged to undergo an idle period.

47. A telecommunications system according to claim 6, wherein in order to operate at reduced transmission power during the slot or slots assigned to its group in the frame assigned to it, each transmitter is arranged to undergo an idle period.

48. A telecommunications system according to claim 7, wherein in order to operate at reduced transmission power during the slot or slots assigned to its group in the frame assigned to it, each transmitter is arranged to undergo an idle period.

49. A telecommunications system according to claim 8, wherein in order to operate at reduced transmission power during the slot or slots assigned to its group in the frame assigned to it, each transmitter is arranged to undergo an idle period.

50. A telecommunications system according to claim 9, wherein in order to operate at reduced transmission power during the slot or slots assigned to its group in the frame assigned to it, each transmitter is arranged to undergo an idle period.

51. A telecommunications system according to claim 2, wherein each transmitter is arranged to operate at reduced transmission power for 0.667ms during the slot or slots assigned to its group in the frame assigned to it.

52. A telecommunications system according to claim 3, wherein each transmitter is arranged to operate at reduced transmission power for 0.667ms during the slot or slots assigned to its group in the frame assigned to it.

53. A telecommunications system according to claim 4, wherein each transmitter is arranged to operate at reduced transmission power for 0.667ms during the slot or slots assigned to its group in the frame assigned to it.

54. A telecommunications system according to claim 5, wherein each transmitter is arranged to operate at reduced transmission power for 0.667ms during the slot or slots assigned to its group in the frame assigned to it.

55. A telecommunications system according to claim 6, wherein each transmitter is arranged to operate at reduced transmission power for 0.667ms during the slot or slots assigned to its group in the frame assigned to it.

56. A telecommunications system according to claim 7, wherein each transmitter is arranged to operate at reduced transmission power for 0.667ms during the slot or slots assigned to its group in the frame assigned to it.

57. A telecommunications system according to claim 8, wherein each transmitter is arranged to operate at reduced transmission power for 0.667ms during the slot or slots assigned to its group in the frame assigned to it.

58. A telecommunications system according to claim 9, wherein each transmitter is arranged to operate at reduced transmission power for 0.667ms during the slot or slots assigned to its group in the frame assigned to it.

59. A telecommunications system according to claim 10, wherein each transmitter is arranged to operate at reduced transmission power for 0.667ms during the slot or slots assigned to its group in the frame assigned to it.

60. A telecommunications system according to claim 2, which is operable according to a W-CDMA system.

61. A telecommunications system according to claim 3, which is operable according to a W-CDMA system.

62. A telecommunications system according to claim 4, which is operable according to a W-CDMA system.

63. A telecommunications system according to claim 5, which is operable according to a W-CDMA system.

64. A telecommunications system according to claim 6, which is operable according to a W-CDMA system.

65. A telecommunications system according to claim 7, which is operable according to a W-CDMA system.

66. A telecommunications system according to claim 8, which is operable according to a W-CDMA system.

67. A telecommunications system according to claim 9, which is operable according to a W-CDMA system.

68. A telecommunications system according to claim 10, which is operable according to a W-CDMA system.

69. A telecommunications system according to claim 11, which is operable according to a W-CDMA system.

70. A telecommunications system according to claim 2, wherein the said period is longer than one slot.

71. A telecommunications system according to claim 3, wherein the said period is longer than one slot.

72. A telecommunications system according to claim 4, wherein the said period is longer than one slot.

73. A telecommunications system according to claim 5, wherein the said period is longer than one slot.

74. A telecommunications system according to claim 6, wherein the said period is longer than one slot.

75. A telecommunications system according to claim 7, wherein the said period is longer than one slot.

76. A telecommunications system according to claim 8, wherein the said period is longer than one slot.

77. A telecommunications system according to claim 9, wherein the said period is longer than one slot.

78. A telecommunications system according to claim 10, wherein the said period is longer than one slot.

79. A telecommunications system according to claim 11, wherein the said period is longer than one slot.

80. A telecommunications system according to claim 12, wherein the said period is longer than one slot.

REMARKS

This preliminary amendment is presented to place the application in proper form for examination and to eliminate multiple dependency from the present claims. No new matter has been added. Early examination and favorable consideration of the above-identified application is earnestly solicited.

Any additional fees or charges required at this time in connection with the application may be charged to our Patent and Trademark Office Deposit Account No. 03-2412.

Respectfully submitted,
COHEN, PONTANI, LIEBERMAN & PAVANE

By: _____



Michael C. Stuart
Reg. No. 35,698
551 Fifth Avenue, Suite 1210
New York, N.Y. 10176
(212) 687-2770

7 January 2002

10/030352

JC10 Rec'd PCT/PTO

07 JAN 2002
By Express Mail # EV052763365US · January 7, 2002

AMENDMENTS TO THE SPECIFICATION AND CLAIMS SHOWING CHANGES

The claims have been amended as follows:

3. A telecommunications system according to **[any preceding]** claim 1, wherein adjacent base stations within a group are assigned different frame numbers.

4. A telecommunications system according to **[any preceding]** claim 1, wherein adjacent base stations belonging to different groups are assigned different frame numbers.

5. A telecommunications system according to **[any preceding]** claim 1, wherein all the base stations within one group are assigned the same slot number or numbers.

6. A telecommunications system according to **[any preceding]** claim 1, wherein each frame comprises 15 slots and geographically adjacent groups are assigned slots which are spaced apart by at least one slot period.

7. A telecommunications system according to **[any preceding]** claim 1, each of the transmitters of each group being assigned more than one frame number.

8. A telecommunications system according to **[any preceding]** claim 1, in which each superframe comprises 72 frames.

9. A telecommunications system according to **[any preceding]** claim 1, wherein the transmitters operate asynchronously.

10. A telecommunications system according to **[any preceding]** claim 1, wherein in order to operate at reduced transmission power during the slot or slots assigned to its group in the frame assigned to it, each transmitter is arranged to undergo an idle period.

11. A telecommunications system according to **[any preceding]** claim 1, wherein each transmitter is arranged to operate at reduced transmission power for 0.667ms during the slot or slots assigned to its group in the frame assigned to it.

12. A telecommunications system according to **[any preceding]** claim 1, which is operable according to a W-CDMA system.

13. A telecommunications system according to **[any preceding]** claim 1, wherein the said period is longer than one slot.

PLACEMENT OF IDLE PERIODS**Description**

The present invention relates to a telecommunications system and in particular to the arrangement of transmitters to potentially allow the transmissions of individual transmitters to be more easily distinguished.

It is known to be desirable in telecommunications systems to provide positioning methods for determining the geographical location of users within the system. This is useful for many reasons, such as emergency location, area-based billing, fleet management for trucking companies and other similar location based value-added services.

One way of mobile phone positioning is by means of a triangulation system, in which the location of a particular mobile phone is calculated using control signals from at least the three base stations closest to it. This system uses the assumption that the distance of the phone from a base station is proportional to the strength of the signal which the base station receives from it, or the time taken for the signal to travel between the phone and the respective base station. Thus the position of the phone can be determined by comparing the relative strengths or travel times of received signals between the three base stations and thus assessing the distance of the user from each base station. The actual location of the user is then obtainable geometrically since the location of the base stations is known and fixed.

There are a number of different methods of making the measurements for performing the above calculation, depending on the mobile system. In a Code Division Multiple Access (CDMA) system, the method which provides the greatest accuracy as well as having other advantages is a time-based method. This method is a downlink method in which a user's mobile phone measures the differences in the time of arrival (TOA)

of signals from surrounding base stations in order to determine the relative distances between the user and each base station.

One particular problem which a time-based method is capable of overcoming is that of "hearability". This problem occurs when the user's mobile phone is much closer to one of the base stations being used for positioning purposes than other surrounding base stations. In this situation, the signal between the user and the close station is so strong, that it is difficult to transmit and receive signals between the user and the other surrounding base stations. This problem occurs particularly in a CDMA system, because all base stations typically transmit at the same carrier frequency.

In the proposed wideband CDMA system (W-CDMA), which is suggested for the universal mobile telecommunications system (UMTS) standard there are proposed to be three types of control channel. The first type is broadcast control channels (BCH) which are to be used, for example, for transmitting frequency and frame synchronisation information. The second type is common control channels (CCCH) which are to be used for network access, for example paging services. These first two types are common to all mobile users. The third type is dedicated control channels which are to be allocated to individual users. These include channels used for handover and user registration. It is likely that measurements for the purpose of mobile phone location will use an existing BCH. Signals are transmitted in blocks called frames, transmitted over each channel. The order of transmission of frames from the different data streams is suitably selected for greatest efficiency. Since this is not a time division system, the problem of hearability can in principle be overcome by transmitting at reduced power or ceasing transmission from the closest base station for short periods of time. Such a time period is known as an idle period. It allows the remaining base stations being used for positioning purposes to communicate with the mobile phone, thus providing the ability to locate the user. This should not affect the transmission quality significantly since during such a time period, a user's mobile phone will often receive signals from its other nearby base stations if the mobile phone is in a soft handover (macrodiversity) situation.

In order to allow positioning to occur during idle periods it would be desirable to allocate idle periods such that nearby base stations do not have idle periods at the same time. This is so that during an idle period, a mobile phone will still be able to pick up signals from other nearby base stations and therefore the positioning of the mobile can continue using signals from other base stations.

According to the present invention there is provided a telecommunications system comprising : a plurality of transmitters capable of transmitting data in superframes, each superframe comprising a plurality of frames, and each frame comprising a plurality of slots; the transmitters being arranged in groups, each group comprising a number of base stations, each group of base stations being assigned one or more slot numbers which are different from those of other groups and each of the transmitters of each group being assigned a different frame number, each transmitter being arranged to operate at reduced transmission power for a period commencing in the allocated slot or slots assigned to its group in the frame assigned to it.

An embodiment of the present invention will now be described by way of example with reference to the accompanying drawings in which :

Figure 1 is a schematic representation of a superframe divided into frames, and the associated time slots; and

Figure 2 is a representation of a two-layer re-use system in one RNC coverage area.

This embodiment relates to a mobile telecommunications system using the proposed W-CDMA standard, in which the network is asynchronous. The following description focuses on control of base stations by radio network controllers (RNCs) and transmission between base stations and mobile telephones.

In the proposed W-CDMA system, a mobile station can communicate by radio with one or more base stations. Each base station is controlled by an RNC, each of

which can control a number of base stations. The RNCs are connected to one or more core network entities which are connected to other telecommunications networks, and by means of which telecommunications services can be provided to the mobile station.

Under normal conditions a base station (BS) transmits signals carrying a variety of data and control information in the form of frames. In this embodiment, there are 72 frames in one superframe and each frame is 10ms long. Thus each superframe is 0.72 seconds long. This is indicated in figure 1. Figure 1 shows a superframe (labelled SUPERFRAME) divided into 72 frames, labelled FRAME 1, FRAME 2, FRAME 3 ... FRAME 72. The number and duration of frames in this embodiment are an example, but there could be a different number of frames in a superframe and the frames could be of a duration different from 10ms. Signals transmitted by a base station may be used for determining the locations of mobile phones .

Figure 1 also shows that in terms of time, each frame is divided into 15 slots, each slot having a length in time of one fifteenth of 10ms, which is approximately 0.667ms. These slots are labelled for illustration for FRAME 1 as SLOT 1.....SLOT 15. Each slot represents one measurement period for positioning purposes, that is to say signal measurements for positioning purposes can be made by the base station approximately every 0.667ms.

In this embodiment, idle periods are scheduled to occur for the duration of one (approximately) 0.667ms slot. Thus when an idle period is scheduled for a particular base station that base station will either cease transmission or transmit at much reduced power for a (approximately) 0.6667ms slot. During this period any mobile phones located near to such a particular base station will continue to receive signals from other base stations near to them, so that positioning of such mobile phones can continue using these other signals. Indeed the reduced signal from the particular base station allows these other signals to be received with much greater accuracy by the mobile phones.

In order for it to be assured that mobile phones can continue to receive signals from other base stations during the idle period of one base station, it is necessary to co-ordinate the occurrence of idle periods of nearby base stations in the mobile network. The assignment of idle periods to base stations is carried out by a radio network controller (RNC) according to a predetermined strategy.

Figure 2 shows how the idle periods are assigned in the present embodiment. This figure shows a part of one RNC coverage area, in which all the base stations are controlled by one RNC. This RNC coverage area can be considered to continue in all directions beyond the part shown and furthermore the telecommunications system can be considered to extend beyond that into other RNC coverage areas, but for the purposes of describing this embodiment, the description of the allocation of idle periods is based on consideration of the seven groups of base stations shown in figure 2. The number seven here is used as an example in this embodiment, but a different number could be chosen. The areas covered by the radio cells of the base stations of each of the seven groups are shown by different shadings and are labelled A-G. In the arrangement shown in the figure, group A is the central group which is surrounded by the other six groups B-G. Group B is situated to the top right of group A and groups C-G are situated in clockwise progression from group B. There are no gaps between the groups. In practice the groups may overlap, or there may be some gap in coverage areas between the groups.

Each of the seven groups A-G contains seven base stations, labelled 1-7. For ease of drawing, each base station is shown as covering a hexagonal area so that there are no uncovered areas. Referring to figure 2, within the hexagonal area of a particular base station, it is assumed that a mobile phone will receive the strongest signal from that base station. In practice the areas would be less uniform, but this would not affect the working of the embodiment significantly. In practice the area covered by a base station depends on factors including intervening features, such as buildings, and the directionality of the base station's antenna. In practice the

coverage areas of adjacent base stations may abut, overlap or be spaced somewhat apart.

It should be understood that any sub-base stations or sectors within the hexagonal area of a base station, for example sub-base stations within an office site, can be synchronised with the base station and allocated idle periods at the same time. This is because positioning of a mobile may be assumed to involve measurements between different base station sites, not between sub-base stations within a site.

In the system of Figure 2 a two-level reuse pattern is used to allocate idle periods. In order to illustrate this concept, the first level reuse pattern will be described with reference to group A.

Group A contains seven base stations, which are a central one, BS1, surrounded by six others, arranged such that BS2 is directly below BS1 and BS3-7 are situated in clockwise progression from BS2. Thus the shape of the area covered by each group is defined by a central hexagon surrounded by six further hexagons joined along adjacent edges. There are no gaps between the areas. It would be possible to number the base stations differently or to use a different number of base stations within a group or to use a different shape to depict the coverage area of a base station. The numbering and arrangement of cells is purely illustrative.

The purpose of the first level of reuse is to ensure that no two of BS1-7 are allocated an idle period at the same time. Therefore the idle periods are allocated in sequence (although other allocation schemes could be used to achieve the same result). This is shown in Table 1 below, for one superframe.

BS number	Assigned frames for idle period
BS1	1 8 15 22 29 36 43 50 57 64
BS2	2 9 16 23 30 37 44 51 58

	65
BS3	3 10 17 24 31 38 45 52 59 66
BS4	4 11 18 25 32 39 46 53 60 67
BS5	5 12 19 26 33 40 47 54 61 68
BS6	6 13 20 27 34 41 48 55 62 69
BS7	7 14 21 28 35 42 49 56 63 70

Table 1 : First level reuse frame allocation for Group A

Since there are seven base stations, the reuse factor in this case is chosen to be 7. This means that the first seven frames of the superframe are assigned sequentially to BS1-7 and then the next seven are similarly assigned (frames 8-14) followed by the next seven (frames 15-21) and so on, until 70 frames have been allocated. Since the superframe consists of 72 frames, frames 71 and 72 are not allocated. Alternatively, frames 71 and 72 could be allocated to any base station. Upon completion of this superframe, the pattern is repeated for the subsequent superframes.

Such an assignment of idle periods means that one idle period is equal to the measurement interval. This is because in this embodiment an idle period occurs throughout one (approximately) 0.667ms time slot, as explained above. The measurement interval is decided according to the required quality of data transmission. The period of (approximately) 0.667ms is in the proposed W-CDMA standard but other periods are compatible with the present invention. In the W-

CDMA standard the performance penalty due to the occurrence of an idle period over this time period is likely to be acceptably small.

Table 1 depicts a uniform assignment of frames having idle periods. An alternative would be to vary the allocation of idle periods so that some base stations were allocated more idle periods than others. This might be useful depending on the number of mobile phones in the area of some base stations at a particular time.

It would also be possible to vary the pattern of allocation between superframes, but this might well add unnecessary complications.

Having considered the first level reuse pattern for group A, referring to figure 2 it can be seen that the other groups B-G are formed from similar arrangements of hexagons defining similar base station coverage areas. Each group is arranged to have a central base station BS1 surrounded by the other six base stations BS2-7, BS2 being directly below BS1 and BS3-7 being situated in clockwise progression from BS2. This means that there is no occurrence of a same-numbered base station from one group being situated adjacent to a same-numbered base station of another group. This means that in this embodiment, each of the groups uses the same first-level reuse pattern as that described above for group A. Therefore it can be arranged that adjacent base stations of different groups will always be assigned different frame numbers for idle periods. There is some uncertainty that this will be the case due to the asynchronicity of the network.

It would be possible to vary the pattern of frame allocation between groups, for example to be non-uniform.

To summarise, the first reuse level defines the frame numbers of the frames containing the idle periods within a superframe for each base station.

The second level reuse pattern will now be described with reference to the entire area depicted in figure 2. The purpose of the second level reuse allocation is to define the location of the start of the idle period within a frame, the frame having been allocated according to the first reuse level. In this embodiment, one slot is allocated for an idle period, but it would be possible to allocate one or more adjacent time slots within a frame during which the base station will have an idle period. Since there are 15 slots within a frame in this embodiment, the maximum second level re-use factor is 15. In general, the maximum reuse factor is given by the following expression :

Integer part of [number of slots in a frame / length of idle period in slots]

The second level reuse pattern is allocated according to groups. This means that all seven base stations in any one group are allocated the same slot number within any given frame. In fact, just odd slot numbers are allocated, as shown in table 2 below.

Group	Slot number
A	1st slot
B	11th slot
C	13th slot
D	3rd slot
E	5th slot
F	7th slot
G	9th slot

Table 2 : Second level reuse slot allocation in one frame

The table indicates that central group A is allocated the first slot of every frame and odd-numbered slots 3-13 are allocated to the remaining groups in a clockwise sequence from group D round to group B.

Such a slot allocation means that for any given group, all seven base stations within that group use the same slot number within their allocated frame. By virtue of the first level frame reuse allocation, namely that different base stations within a group are allocated different frames, the risk of allocated idle periods of adjacent base stations within a group occurring at the same time is small. The risk is not zero, due to the asynchronicity between base stations. Furthermore, since adjacent base stations of different groups are allocated both different frame numbers and slot numbers, the risk of their idle periods occurring at the same time is similarly small.

In practical terms, since the separation in time between consecutive idle periods is a constant, measurement delays which happen as a result of an idle period do not depend on the time at which a mobile positioning update is requested. Hence the effect on service quality is likely to be small.

Thus, in summary, the base stations are split into groups of adjacent or at least nearby base stations which may or may not be controlled by a single RNC. The base stations in each group are each allocated selected frames of the recurring superframes of the transmission structure such that in each group no more than one base station is allocated any frame. Between adjacent or at least nearby groups an allocation of idle periods as selected slots in the recurring frames of the transmission structure is made such that no more than one group in a locality is allocated any slot. By this means the likelihood of any more than one base station in a locality having an idle period at any time is greatly reduced. Hence, the opportunity for a mobile station to reliably measure the signals transmitted from the base stations can be increased and the accuracy of positioning measurements can potentially be improved.

It will be appreciated that the embodiment would be implemented in a similar way in the surrounding RNC coverage areas, such that the risk of idle periods of base stations adjacent to one another but falling within a different RNC coverage area occurring at the same time, is also similarly small.

According to this embodiment, in any one frame each base station is allocated just one idle slot out of the 15 available, meaning that each idle period lasts for a duration of one slot, or approximately 0.667ms. It would be possible to vary the idle period duration by allocating other multiples of slots to a base station, for example half a slot, two or more slots or even a whole frame. It would also be possible, for example, to allocate more than two slots to some base stations and none to others depending on requirements, thus varying the duration of each base station's idle period. It would also be possible to not allocate any slots for some frames and hence reduce the total number of idle periods within a superframe and thus increase the service quality.

The embodiment described is concerned with minimising the chance of idle periods of adjacent base stations from coinciding. Since the allocation of frames and slot numbers is flexible, it would be possible to number the base stations differently or locate the groups differently should it be desired to use different criteria for optimum idle period allocation. The described idle period allocation would also work across RNC coverage areas.

The described embodiment is for an asynchronous network. It allows the probability of idle periods of nearby base stations overlapping to be small. The embodiment and its mentioned alternatives would work equally well with a synchronous network and in that case would in fact guarantee no overlap.

CLAIMS

1. A telecommunications system comprising :
a plurality of transmitters capable of transmitting data in superframes, each superframe comprising a plurality of frames, and each frame comprising a plurality of slots;
the transmitters being arranged in groups, each group comprising a number of base stations, each group of base stations being assigned one or more slot numbers which are different from those of other groups and each of the transmitters of each group being assigned a different frame number, each transmitter being arranged to operate at reduced transmission power for a period commencing in the allocated slot or slots assigned to its group in the frame assigned to it.
2. A telecommunications system according to claim 1, wherein each group comprises a set of nearby transmitters.
3. A telecommunications system according to any preceding claim, wherein adjacent base stations within a group are assigned different frame numbers.
4. A telecommunications system according to any preceding claim, wherein adjacent base stations belonging to different groups are assigned different frame numbers.
5. A telecommunications system according to any preceding claim, wherein all the base stations within one group are assigned the same slot number or numbers.
6. A telecommunications system according to any preceding claim, wherein each frame comprises 15 slots and geographically adjacent groups are assigned slots which are spaced apart by at least one slot period.

7. A telecommunications system according to any preceding claim, each of the transmitters of each group being assigned more than one frame number.
8. A telecommunications system according to any preceding claim, in which each superframe comprises 72 frames.
9. A telecommunications system according to any preceding claim, wherein the transmitters operate asynchronously.
10. A telecommunications system according to any preceding claim, wherein in order to operate at reduced transmission power during the slot or slots assigned to its group in the frame assigned to it, each transmitter is arranged to undergo an idle period.
11. A telecommunications system according to any preceding claim, wherein each transmitter is arranged to operate at reduced transmission power for 0.667ms during the slot or slots assigned to its group in the frame assigned to it.
12. A telecommunications system according to any preceding claim, which is operable according to a W-CDMA system.
13. A telecommunications system according to any preceding claim, wherein the said period is longer than one slot.
14. A telecommunications system according to any preceding claim, substantially as herein described with reference to the accompanying drawings.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 January 2001 (18.01.2001)

PCT

(10) International Publication Number
WO 01/05163 A3

(51) International Patent Classification⁷: **H04Q 7/38**

(21) International Application Number: **PCT/IB00/01719**

(22) International Filing Date: **7 July 2000 (07.07.2000)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
9916220.8 **9 July 1999 (09.07.1999)** **GB**

(71) Applicant (for all designated States except US): **NOKIA NETWORKS OY** [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **KALLIOJARVI, Kari** [FI/FI]; Nokia Networks Oy, Keilalahdentie 4, FIN-02150 Espoo (FI). **MODONESI, Isabella** [FI/FI]; Nokia Networks Oy, Keilalahdentie 4, FIN-02150 Espoo (FI).

(74) Agents: **SLINGSBY, Philip, Roy et al.**; Page White & Farrer, 54 Doughty Street, London WC1N 2LS (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).


Published:

— With international search report.

(88) Date of publication of the international search report:
14 June 2001

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **PLACEMENT OF IDLE PERIODS**



(57) Abstract: A telecommunications system comprising: a plurality of transmitters capable of transmitting data in superframes, each superframe comprising a plurality of frames, and each frame comprising a plurality of slots; the transmitters being arranged in groups, each group comprising a number of base stations, each group of base stations being assigned one or more slot numbers which are different from those of other groups and each of the transmitters of each group being assigned a different frame number, each transmitter being arranged to operate at reduced transmission power for a period commencing in the allocated slot or slots assigned to its group in the frame assigned to it.

2552997

WO 01/05163 A3




FIG. 1

2/2




FIG. 2

COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY
Includes Reference to PCT International Applications

Attorney's Docket
No. **4925-198PUS**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

PLACEMENT OF IDLE PERIODS

the specification of which (check only one item below)

☐ is attached hereto

☐ was filed as United States application

Serial No. _

on _

and was amended

on _ (if applicable).

☒ was filed as PCT international application

Number PCT/IB00/01719 ✓

on 07 July 2000 ✓

and was amended under PCT Article 19

on _ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of the application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed.

PRIOR FOREIGN/PCT APPLICATIONS AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. 119:

Country (if PCT, indicate "PCT")	Application Number	Date of Filing (day, month, year)	Priority Claimed Under 35 U.S.C. 119	
Great Britain	9916220.8 ✓	09 July 1999 ✓	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO
PCT	PCT/IB00/01719 ✓	07 July 2000 ✓	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO

Combined Declaration for Patent Application and Power of Attorney (Continued)
(Includes Reference to PCT International Applications)

Attorney's Docket No.
4925-198PUS

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application:

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. 120:

U.S. APPLICATIONS		STATUS (check one)		
U.S. APPLICATION NUMBER	U.S. FILING DATE	PATENTED	PENDING	ABANDONED
PCT APPLICATIONS DESIGNATING THE U.S.				
PCT APPLICATION NO.	PCT FILING DATE	U.S. SERIAL NUMBERS ASSIGNED (if any)		
PCT/IB00/01719 ✓	07 July 2000 ✓		x	

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (*List name and registration number*)

MYRON COHEN, Reg. No. 17,358; THOMAS C. PONTANI, Reg. No. 29,763; LANCE J. LIEBERMAN, Reg. No. 28,437; MARTIN B. PAVANE, Reg. No. 28,337; MICHAEL C. STUART, Reg. No. 35,698; KLAUS P. STOFFEL, Reg. No. 31,668; EDWARD WEISZ, Reg. No. 37,257; VINCENT M. FAZZARI, Reg. No. 26,879; JULIA S. KIM, Reg. No. 36,567; ALFRED FROEBRICH, Reg. No. 38,887; ALFRED H. HEMINGWAY, JR., Reg. No. 26,736; KENT H. CHENG, Reg. No. 33,849; YUNLING REN, Reg. No. 47,019; ROGER S. THOMPSON, Reg. No. 29,594; BRICE FALLER, Reg. No. 29,532; DAVID J. ROSENBLUM, Reg. No. 37,709; TONY CHEN, Reg. No. 44,607; ELI WEISS, Reg. No. 17,765.

Send correspondence to:
Michael C. Stuart
Reg. No. 35,698
Cohen, Pontani, Lieberman & Pavane
551 Fifth Avenue, Suite 1210
New York, New York 10176

Direct Telephone calls to:
(name and telephone number)
Michael C. Stuart
(212) 687-2770

201	FULL NAME OF INVENTOR	FAMILY NAME KALLIOJARVI	FIRST GIVEN NAME Kari	SECOND GIVEN NAME
	RESIDENCE, CITIZENSHIP	CITY Espoo	STATE OR FOREIGN COUNTRY Finland	COUNTRY OF CITIZENSHIP Finland
	POST OFFICE ADDRESS	POST OFFICE ADDRESS Keilalahdentie 4	CITY Espoo	STATE & ZIP CODE/COUNTRY FIN-02150 Finland
202	FULL NAME OF INVENTOR	FAMILY NAME MODONESI	FIRST GIVEN NAME Isabella	SECOND GIVEN NAME
	RESIDENCE, CITIZENSHIP	CITY Espoo De Bilt NLX	STATE OR FOREIGN COUNTRY Finland The Netherlands	COUNTRY OF CITIZENSHIP Finland Italy ✓
	POST OFFICE ADDRESS	POST OFFICE ADDRESS Keilalahdentie 4	CITY Espoo De Bilt	STATE & ZIP CODE/COUNTRY FIN-02150 Finland

Hessenweg 9B

The Netherlands

changed
16-04-2002

Combined Declaration for Patent Application and Power of Attorney (Continued) (Includes Reference to PCT International Applications)				Attorney's Docket No. 4925-198PUS
2 0 3	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
	RESIDENCE, CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
	POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE & ZIP CODE/COUNTRY
<p>I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under §1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.</p>				
SIGNATURE OF INVENTOR 201		SIGNATURE OF INVENTOR 202 <i>[Signature]</i>		SIGNATURE OF INVENTOR 203
DATE		DATE <i>16-04-2002</i>		DATE

COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY
Includes Reference to PCT International Applications

Attorney's Docket
No. 4925-198PUS

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

PLACEMENT OF IDLE PERIODS

the specification of which (check only one item below)

☐ is attached hereto

☐ was filed as United States application

Serial No. _

on _

and was amended

on _ (if applicable).

☒ was filed as PCT international application

Number PCT/IB00/01719

on 07 July 2000

and was amended under PCT Article 19

on _ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of the application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed.

PRIOR FOREIGN/PCT APPLICATIONS AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. 119:

Country (if PCT, indicate "PCT")	Application Number	Date of Filing (day, month, year)	Priority Claimed Under 35 U.S.C. 119	
Great Britain	9916220.8	09 July 1999	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO
PCT	PCT/IB00/01719	07 July 2000	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO
			<input type="checkbox"/> YES	<input type="checkbox"/> NO

Combined Declaration for Patent Application and Power of Attorney (Continued) (Includes Reference to PCT International Applications)				Attorney's Docket No. 4925-198PUS
2 0 3	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
	RESIDENT, CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
	POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE & ZIP CODE/COUNTRY
<p>I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under §1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.</p>				
SIGNATURE OF INVENTOR 201 <i>Karl Hall</i>		SIGNATURE OF INVENTOR 202		SIGNATURE OF INVENTOR 203
DATE MARCH 19, 2002		DATE		DATE

Combined Declaration for Patent Application and Power of Attorney (Continued)
(Includes Reference to PCT International Applications)

Attorney's Docket No.
4925-198PUS

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application:

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. 120:

U.S. APPLICATIONS		STATUS (check one)		
U.S. APPLICATION NUMBER	U.S. FILING DATE	PATENTED	PENDING	ABANDONED
PCT APPLICATIONS DESIGNATING THE U.S.				
PCT APPLICATION NO	PCT FILING DATE	U.S. SERIAL NUMBERS ASSIGNED (if any)		
PCT/IB00/01719 ✓	07 July 2000 ✓		x	

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (*List name and registration number*)


MYRON COHEN, Reg. No. 17,358; THOMAS C. PONTANI, Reg. No. 29,763; LANCE J. LIEBERMAN, Reg. No. 28,437; MARTIN B. PAVANE, Reg. No. 28,337; MICHAEL C. STUART, Reg. No. 35,698; KLAUS P. STOFFEL, Reg. No. 31,668; EDWARD WEISZ, Reg. No. 37,257; VINCENT M. FAZZARI, Reg. No. 26,879; JULIA S. KIM, Reg. No. 36,567; ALFRED FROEBRICH, Reg. No. 38,887; ALFRED H. HEMINGWAY, JR., Reg. No. 26,736; KENT H. CHENG, Reg. No. 33,849; YUNLING REN, Reg. No. 47,019; ROGER S. THOMPSON, Reg. No. 29,594; BRICE FALLER, Reg. No. 29,532; DAVID J. ROSENBLUM, Reg. No. 37,709; TONY CHEN, Reg. No. 44,607; ELI WEISS, Reg. No. 17,765.

Send correspondence to:
Michael C. Stuart
Reg. No. 35,698
Cohen, Pontani, Lieberman & Pavane
551 Fifth Avenue, Suite 1210
New York, New York 10176

Direct Telephone calls to:
(name and telephone number)
Michael C. Stuart
(212) 687-2770

201	FULL NAME OF INVENTOR	FAMILY NAME <u>KALLIOJARVI</u>	FIRST GIVEN NAME <u>Kari</u>	SECOND GIVEN NAME
	RESIDENCE, CITIZENSHIP	CITY <u>Espoo</u> <u>FIN</u>	STATE OR FOREIGN COUNTRY <u>Finland</u>	COUNTRY OF CITIZENSHIP <u>Finland</u> ✓
	POST OFFICE ADDRESS	POST OFFICE ADDRESS <u>Keilalahdentie 4</u>	CITY <u>Espoo</u>	STATE & ZIP CODE/COUNTRY <u>FIN-02150 Finland</u>
202	FULL NAME OF INVENTOR	FAMILY NAME <u>MODONESI</u>	FIRST GIVEN NAME <u>Isabella</u>	SECOND GIVEN NAME
	RESIDENCE, CITIZENSHIP	CITY <u>Espoo</u>	STATE OR FOREIGN COUNTRY <u>Finland</u>	COUNTRY OF CITIZENSHIP <u>Finland</u>
	POST OFFICE ADDRESS	POST OFFICE ADDRESS <u>Keilalahdentie 4</u>	CITY <u>Espoo</u>	STATE & ZIP CODE/COUNTRY <u>FIN-02150 Finland</u>

United States Patent & Trademark Office
Office of Initial Patent Examination -- Scanning Division



Application deficiencies found during scanning:

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

☐ *Scanned copy is best available. fig 2 is dark.*